



Staining tanks "Colour Com" made from glass.



Staining tank with screw cap hermetically sealed lid.

### STAINING TANK

Part No.	Type	Height / Width / Depth (exterior) mm			Slide quantity	Applications
1001138	1	85	105	70	10 of 76 x 26 mm	Tank with lid, requires rack No. 2 that is placed inside.
1001139	2	30	90	48	10 of 76 x 26 mm	Tank rack, bottomless, submerge in No.1 tank.
1001140	3	105	60	55	16 of 76 x 26 mm	Hellendahl vertical tank with lid.
1001141	4	50	85	70	10 of 76 x 26 mm	Horizontal staining tank with lid.
1001142	5	105	45	45	10 of 76 x 26 mm	Coplin, vertical staining tank with lid.
1001352	6	110	56	56	10 of 76 x 26 mm	Coplin, staining tank made of polyethylene with lid.



### 1. ANGLE FORM MOULDS

For paraffin wax covers.

Supplied as two separate angular plates made of AISI 304 stainless steel.

Part No.	Height / Width / Depth (usable mould) mm			Part No.	Height / Width / Depth (usable mould) mm		
6051622	14	22	44	6051645	20	45	85
6051635	20	35	65	6051690	25	90	150

### 2. ROUND INSERT MOULDS

Made of perforated AISI 304 stainless steel with lid.

Part No.	Ø mm	Height mm
1051837	37	8



## Cooling bath "Refricub"

ELECTRONIC CONTROL WITH DIGITAL DISPLAY  
ADJUSTABLE TEMPERATURE DOWN TO -25 °C.

### APPLICATIONS

Suitable for maintaining paraffin wax and waxes in a solid form for long periods of time, etc.

### FEATURES

Temperature homogeneity:  $\pm 2$  °C.

Precision of temperature controller: 1 °C.

External case made of epoxy covered metal with AISI 304 stainless steel tank and top.

An anti vibration hermetically sealed CFC free compressor is mounted in the base of the unit, supplied with ventilated evaporator, regulating valve and condenser.

### CONTROL PANEL

Illuminated mains indicator switch.

Electronic controller for temperature with two digit digital display with a resolution of:  $\pm 1$  digit.

PTC probe.

Part No.	Capacity litres	Height/Width/Depth (tank) cm			Height/Width/Depth (exterior) cm			Power HP	Power W	Weight Kg
4100519	18	20	30	31	80	46	44	3/8	350	22

