



Storage refrigerators “Stocklow” LS, GS and LSC

WITH FAN ASSISTED CIRCULATION.

MODEL LS, WITH METAL DOOR. TEMPERATURE CONTROLLABLE FROM +1 °C TO +8 °C.

MODEL GS, WITH DOUBLE GLAZED ANTI MIST DOOR. TEMPERATURE CONTROLLABLE FROM +1 °C TO +8 °C.

MODEL LSC, WITH METAL DOOR. TEMPERATURE CONTROLLABLE FROM -17 °C TO -22 °C.



NEW DESIGN

APPLICATIONS

Preservation and storage of products that require below ambient temperatures.

FEATURES

Chemically resistant.
Tropical hermetic compressor.
Automatic defrost with electrical water evaporation system.
Support rack and shelves.
Adjustable front level supports (Models LS and GS).
Supplied with wheels (Model LSC).
The door can be hung to open left or right.
Door lock.

There are two versions:

Stocklow LS and LSC which is completely made of metal, both interior and exterior, AISI 304 stainless steel door.

Stocklow GS inside made of AISI 304 stainless steel and epoxy white external case with glazed door that enables internal view.

CONTROL PANEL

Mains power, ON/OFF switch.
Electronic temperature regulator.
Digital temperature display.
Interior light only (Double glazed door model).

SPARE PARTS

Código **1001858** Set 2 guides + additional tray



Model Stocklow LS and LSC, with metallic door.



Model Stocklow GS, with metallic door.

MODELS	Part No.	Capacity litres	Door	Height / Width / Depth (interior) cm	Height / Width / Depth (exterior) cm	Number of shelves	Power W	Weight Kg
STOCKLOW LS	2101283	600	Metallic	154 61 63	213 73 84	3	250	120
STOCKLOW GS	2101284	600	Glass	154 61 63	213 73 84	3	250	125
STOCKLOW LSC	2101289	600	Metallic	154 61 63	213 73 84	3	500	125

Comes complete with steel shelves, PVC laminated.



Chest Freezers “Combatep”

CONTROLLABLE TEMPERATURE RANGE FROM -14 °C TO -28 °C.

CONTROLLABLE TEMPERATURE RANGE FROM -10 °C TO -40 °C.

APPLICATIONS

Suitable for preservation and freezing of sample.

FEATURES

Epoxy covered external case. Interior of aluminium, with guide supports for baskets or trays.
The interior of the door is made of easy to clean, strong, chemically resistant, moulded ABS.
Drop down lockable door with compensating support hinges. Hermetically sealed compressor, silent and vibration free.

Automatic interior light when the door is opened. (all models except Combatep S-30.)

Digital electronic temperature control.
N.T.C. Sensor.

CONTROL PANEL

Temperature control.
Digital live and preset temperature display.
Push-button temperature selector.



MODELS	Part No.	Capacity litres	Freezing capacity in 24hrs Kg	Temperature up to °C	Height / Width / Depth (interior) cm	Height / Width / Depth (exterior) cm	Power W	Weight Kg
COMBATEMP S-30	2101040	206	28	-28	74 63 53	92 75 71	160	38
COMBATEMP L-30	2101041	343	38	-28	74 100 53	92 113 71	200	56
COMBATEMP S-40	2101181	215	30	-40	63 89 41	92 113 76	230	57
COMBATEMP L-40	2101182	352	40	-40	65 117 50	92 137 81	400	72

Note: Part No. 2101040 is supplied with 1 basket. Part No. 2101041 is supplied with 2 baskets. Part No. 2101181 is supplied with 3 baskets and Part No. 2101182 is supplied with 2 baskets.

SPARE PARTS Baskets

For Combatep. Part No.	2101040 / 2101041	2101181	2101182
Baskets	1001810	1001811	1001812