

COMECTA Orbital shaker "AG-200", "AG-200-A", "AG-200-B"



ELECTRONIC DIGITAL CONTROL OF SPEED AND RUN-TIME

COMMON FEATURES

External ABS case with adapter platform for the different models. Innovative single button to select start, shaking speed, time and stop. Digital display of time and shaking speed.

Maintenance free induction drive motor which produces a uniform movement according to the rotation speed program.

Acoustic notification at the end of the cycle.



Main switch.

Single button selector for shaking speed and time. Display indicating the shaking speed. Display indicating the programmed time.

Measures: Alto 10 x Ancho 28 x fondo 26

TECHNICAL INFORMATION

Rotation frequency: 50-250 r.p.m. Timer from 1 min to 99h 59 min Rotation amplitude: 20mm

Power: 50 W.

Power supply: 220V/50Hz Load capacity: till 2.5Kg

Measures cm: Height 10 x Width 28 x Depth 26



Shaker for Petri plates "AG-200"

With non-slip rubber platform of 24cm width and 20cm depth. Capacity for 4 Petri plates.

Useful for slides and little flasks shaking.

Weight (Kg): 7. Part no: 5312010



Shaker for bottles "AG-200-A"

With non-slip rubber platform of 26cm width and 22cm depth, with 3 adjustable rubber retaining bars suitable for any kind of glasses: Erlenmeyer, flasks, bottles, etc.

Weight (Kg): 8 Part no: 5312011



Shaker for Erlenmeyer flasks "AG-200-B"

Tempered aluminium base of 27cm width and 22cm depth, with multi-adapter location holes to support different capacities flasks from 50ml to 2000ml.

Weight (Kg): 8. Part no: 5312012



Made of stainless steel with upper spring. Part no. 5312013 Adapter for 50 ml. Platform capacity: 12 units Part no. 5312014 Adapter for 100 ml. Platform capacity: 8 units Part no. 5312015 Adapter for 250 ml.

Platform capacity: 6 units Part no. 5312016 Adapter for 500 ml. Platform capacity: 4 units

Part no. 5312017 Adapter for 1000 ml.

Platform capacity: 2 units



